

**Amendments to the Claims**

The text of all pending claims and the status of each claim is identified below:

1-10. (Canceled)

11. (Currently Amended) A reaming head, comprising:

a body having a longitudinal axis and an outer surface defining a longitudinally extending substantially cylindrical configuration extending over a majority of the circumference of said outer surface and a truncated surface interrupting said substantially cylindrical configuration;

a cutting element positioned in said truncated surface;

a transverse axis, transverse to the longitudinal axis, the transverse axis intercepting at least a portion of the substantially cylindrical configuration, and intercepting at least a portion of the cutting element;

wherein said cutting element is a blade spaced from said outer surface and extending in substantial alignment with said longitudinal axis.

12. (Previously Presented) The reaming head of claim 11, further including a rounded leading surface adjacent said cylindrical configuration.

13. (Original) A method of eccentric reaming, comprising: providing a reaming head having an outer surface with a cylindrical portion and a cutting element positioned opposite said cylindrical portion and configured for cutting upon oscillatory motion; inserting the reaming head into a bone opening; positioning said cylindrical portion adjacent tissue to be preserved; positioning the cutting surface adjacent tissue to be removed; oscillating the head of the reamer to cause the cutting surface to remove tissue.

14. (Original) The method of claim 13, wherein said oscillating occurs over a range of 20 to 180 degrees.

15. (Original) The method of claim 14, wherein said oscillating occurs over a range of 80 to 120 degrees.

16. (Original) The method of claim 13, wherein said inserting further includes positioning a wire guide into the tissue and positioning the reamer over the wire guide prior to said inserting.

17. (Currently Amended) A reaming head, comprising:

a body having a longitudinal axis and an outer surface defining a longitudinally extending substantially cylindrical configuration extending over a majority of the circumference of said outer surface and a truncated surface interrupting said substantially cylindrical configuration;

a cutting element positioned in said truncated surface and spaced from said outer surface;

a transverse axis, transverse to the longitudinal axis, the transverse axis intercepting at least a portion of the substantially cylindrical configuration, and intercepting at least a portion of the cutting element;

wherein said longitudinally extending substantially cylindrical configuration extends over an arc of at least 240° of the circumference of said outer surface.

18. (Previously Presented) The reaming head of claim 11, wherein said longitudinally extending substantially cylindrical configuration is substantially uninterrupted.

19. (Previously Presented) The reaming head of claim 11, wherein said longitudinally extending substantially cylindrical configuration consists essentially of a single longitudinally extending substantially cylindrical configuration.

20. (Previously Presented) The reaming head of claim 11, wherein said cutting element consists essentially of a single cutting element.

21. (Previously Presented) The reaming head of claim 11, further comprising a guide wire lumen.

22. (Canceled)

23. (Currently Amended) A reaming head, comprising:

a body having a longitudinal axis and a perpendicular axis perpendicular to the longitudinal axis;

an outer surface disposed on a first side of the body,

a truncated surface disposed on a second side of the body;

a cutting element positioned in said truncated surface and spaced from said outer surface;

a first end of the perpendicular axis intercepting at least a portion of the outer surface, and a second end of the perpendicular axis intercepting at least a portion of the truncated surface; wherein said cutting element comprises a blade extending in substantial alignment with said longitudinal axis.

24. (Previously Presented) The reaming head of claim 23, further including a rounded leading surface adjacent said outer surface.

25. (Previously Presented) The reaming head of claim 23, wherein said outer surface extends over an arc of at least a majority of a circumference of said body.

26. (Currently Amended) A reaming head, comprising:

a body having a longitudinal axis and a perpendicular axis perpendicular to the longitudinal axis;  
an outer surface disposed on a first side of the body,  
a truncated surface disposed on a second side of the body;  
a cutting element positioned in said truncated surface and spaced from said outer surface;  
a first end of the perpendicular axis intercepting at least a portion of the outer surface, and a second end of the perpendicular axis intercepting at least a portion of the truncated surface;  
wherein said outer surface extends over an arc of at least 240° of a circumference of said body.

27. (Previously Presented) The reaming head of claim 23, wherein said outer surface is substantially uninterrupted.

28. (Previously Presented) The reaming head of claim 23, wherein said cutting element consists essentially of a single cutting element.

29. (Previously Presented) The reaming head of claim 23, further comprising a guide wire lumen.

30. (Previously Presented) The reaming head of claim 17, further including a rounded leading surface adjacent said cylindrical configuration.

31. (Previously Presented) The reaming head of claim 17, wherein said longitudinally extending substantially cylindrical configuration is substantially uninterrupted.

32. (Previously Presented) The reaming head of claim 17, wherein said longitudinally extending substantially cylindrical configuration consists essentially of a single longitudinally extending substantially cylindrical configuration.
33. (Previously Presented) The reaming head of claim 17, wherein said cutting element consists essentially of a single cutting element.
34. (Previously Presented) The reaming head of claim 17, further comprising a guide wire lumen.
35. (Previously Presented) The reaming head of claim 26, further including a rounded leading surface adjacent said outer surface.
36. (Previously Presented) The reaming head of claim 26, wherein said outer surface extends over an arc of at least a majority of a circumference of said body.
37. (Previously Presented) The reaming head of claim 26, wherein said outer surface is substantially uninterrupted.
38. (Previously Presented) The reaming head of claim 26, wherein said cutting element consists essentially of a single cutting element.
39. (Previously Presented) The reaming head of claim 26, further comprising a guide wire lumen.